

Fax: +49 (0) 23 30/63-355

Dörken GmbH & Co. KG
 Wetterstraße 58
 D-58313 Herdecke
 Germany

DELTA[®]-MAXX Specifications

Item	Quantity	Description	Unit Price	Total Price
1 m ²	<p>DELTA[®]-MAXX (manufacturer: Dörken GmbH & Co. KG, D-58311 Herdecke, Germany) – to be supplied as vapour permeable roofing underlay made of polyester non-woven fabric with a polyurethane coating, and properly laid in accordance with standard roofing procedures and manufacturer's specifications. To be fixed to the rafters with wide-head nails or staples.</p> <p>Weight approx. 190 g/m² Tensile strength approx. 350 N/5 cm conforming to DIN EN 12311 Fire resistance B1 rating (DIN 4102) S_d value approx. 0.15 m</p>		
2 nos	<p>Any small items that protrude through the roof, e.g. air vents, soil pipes, aerials, should be fixed to the underlay with an airtight seal using DELTA[®]-FLEXX TAPE.</p> <p>DELTA[®]-FLEXX TAPE - Special, stretchable, adhesive tape - Top layer of tough, non-woven material - Recommended for use at temperatures of 5 °C and above - Width: 100 mm - Length: 10 m</p>		
3 m	<p>Joints between DELTA[®]-MAXX and skylights or dormer windows, glass tiles, chimneys etc. should be formed so that water cannot get in, but is instead guided past via a channel in the sheet at the point where the cut-out occurs.</p>		