

Fax: +49/23 30/63-355

Dörken GmbH & Co. KG
 Wetterstraße 58
 D-58313 Herdecke
 Germany

Specification DELTA®-VENT N/DELTA®-VENT N PLUS

Item	Qty.	Description	Unit Price	Total Price
1 m ²	<p>DELTA®-VENT N breather underlay (manufacturer: Dörken GmbH & Co. KG, D-58311 Herdecke / Germany) – 3-layer composite breather membrane – to be supplied and installed on rafters in a workmanlike manner in accordance with standard roofing procedures and manufacturer’s specifications and fixed on rafters with staples or wide-head nails.</p> <p>Area weight approx. 120 g/m² Tensile strength approx. 210/155 N/5 cm (DIN EN 12311) Fire-resistance B2 rating/DIN 4102 S_d value approx. 0.02 m</p>		
2 m ²	<p>DELTA®-VENT N PLUS breather underlay (manufacturer: Dörken GmbH & Co. KG, D-58311 Herdecke / Germany) – 3-layer composite breather membrane with integrated self-adhesive edge – to be supplied and installed on rafters in a workmanlike manner in accordance with standard roofing procedures and manufacturer’s specifications and fixed on rafters with staples or wide-head nails.</p> <p>Area weight approx. 120 g/m² Tensile strength approx. 210/155 N/5 cm (DIN EN 12311) Fire-resistance B2 rating/DIN 4102 S_d value approx. 0.02 m</p>		
3	<p>Connections to skylights, dormer windows, chimneys etc. Shall be watertight and include sheet troughs leading around penetrations.</p>		

STANDARD QUALITY