

**Fax: +49/23 30/63-355**

Dörken GmbH & Co. KG  
 Wetterstraße 58  
 D-58313 Herdecke  
 Germany

## Specification DELTA®-VENT S/DELTA®-VENT S PLUS

Item	Qty.	Description	Unit Price	Total Price
1	..... m <sup>2</sup>	<p><b>DELTA®-VENT S</b> breather underlay (manufacturer: Dörken GmbH &amp; Co. KG, D-58311 Herdecke/Germany) – 3-layer composite breather membrane – to be supplied and installed on sheathing in a workmanlike manner in accordance with standard roofing procedures and manufacturer’s specifications and fixed on sheathing with staples or wide-head nails. Fixing to be done on ridge-side edge of DELTA®-VENT S and covered by overlap.</p> <p>Area weight approx. 140 g/m<sup>2</sup>            Tensile strength approx. 250/200 N/5 cm (DIN EN 12311)</p> <p>Fire-resistance B2 rating/DIN 4102            S<sub>d</sub> value approx. 0.02 m</p>		
2	..... m <sup>2</sup>	<p><b>DELTA®-VENT S PLUS</b> breather underlay (manufacturer: Dörken GmbH &amp; Co. KG, D-58311 Herdecke/Germany) – 3-layer composite breather membrane with integrated self-adhesive edge – to be supplied and installed on sheathing in a workmanlike manner in accordance with standard roofing procedures and manufacturer’s specifications and fixed on sheathing with staples or wide-head nails. Fixing to be done on ridge-side edge of DELTA®-VENT S and covered by overlap.</p> <p>Area weight approx. 140 g/m<sup>2</sup>            Tensile strength approx. 250/200 N/5 cm (DIN EN 12311)</p> <p>Fire-resistance B2 rating/DIN 4102            S<sub>d</sub> value approx. 0.02 m</p>		
3	..... m	<p><b>DELTA®-NAGELDICHTUNGSBAND (DELTA®-NB 50)</b>, to be supplied and installed on DELTA®-VENT S beneath counter battens.</p>		
4	.....	<p>Connections to skylights, dormer windows, chimneys etc. Shall be watertight and include sheet troughs leading around penetrations.</p>		